



Wheel-Rail Interface Guidance


CALL
0121 214 7107


EMAIL
info@lrssb.co.uk


WEB
www.lrssb.org


TWITTER
[@LightRailSSB](https://twitter.com/LightRailSSB)


LINKEDIN
[@lighttrailssb](https://www.linkedin.com/company/lighttrailssb)

	WHEEL-RAIL INTERFACE GUIDANCE		LRSSB - LRG - 16.0	
			Issue	01
			Revision	01
			Date	24/05/2023
			Page	1 of 22

TITLE:		WHEEL-RAIL INTERFACE GUIDANCE				
REF:		LRG 16.0		STATUS:	FINAL	
ISSUE:		01	REVISION:	01	DATE:	24/05/2023
DEPT:		LRSSB Safety Assurance			REVIEW DUE:	24/05/2028
DOCUMENT OWNER:				DISTRIBUTION:		
LRSSB				ALL UK TRAMWAYS		
DESCRIPTION:						
THIS DOCUMENT PROVIDES GUIDANCE ON THE INTERFACE BETWEEN WHEELS AND RAILS						
EXPLANATORY NOTE:						
The Light Rail Safety Standards Board is not a regulatory body and compliance with Guidance Notes or Approved Codes of Practice is not mandatory; they reflect good practice and are advisory only. Users are recommended to evaluate the guidance against their own arrangements in a structured and systematic way, noting that parts of the guidance may not be appropriate to their operations. It is recommended that this process of evaluation and any subsequent decision to adopt (or not adopt) elements of the guidance should be documented. Compliance with any or all the contents herein, is entirely at an organisation’s own discretion.						
SOURCE / RELATED DOCUMENTS:						
LRG 1.0 Tramway Principles and Guidance (TPG) (LRSSB) LRG 34.0 Guidance on Control of Contracted Works Determination of Tramway Wheel and Rail Profiles to Minimise Derailment (RTU report 90/3/A) Allen P and Bevan A, Manchester Metropolitan University February 2008 A Good Practice Guide for Managing the Wheel-Rail Interface of Light Rail and Tramway Systems (RTU report 90/3/B) Stow J and Allen P, Manchester Metropolitan University February 2008 Local and Regional Railway Tracks in Germany (in German and English), VDV, Cologne 2007 (ISBN 978-3-87094-674-6) BS EN 13232-3 Railway applications - Track - Switches and crossings - Part 3: Requirements for wheel/rail interaction A survey of UK tram and light railway systems relating to the wheel/rail interface FE/04/14 E J Hollis Health and Safety Laboratory 2006						
RELATED TRAINING COURSES:			RELATED LEGISLATION:			
Understanding Derailments			Health and Safety at Work Act etc. 1974 Railways and Other Guided Transport Systems (Safety) Regulations 2006 (ROGS 2006) (as amended)			
CHANGE NOTES:						
Date of Issue	Issue No.	Revision No.	Reviewer	Details of Revision		
24/05/2023	01	01	LRSSB	Amendments to text / format		
UNCONTROLLED WHEN PRINTED						

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	2 of 22

LRSSB

DOCUMENT CODE: LRG 16.0

WHEEL-RAIL INTERFACE GUIDANCE

CONTENTS

1. Introduction
2. Scope
3. Wheel-Rail Interface Specification
4. Contractual Arrangements
5. Standards
6. Inspection and Monitoring
7. Maintenance
8. Operation Management

Appendices

Appendix 1 Checklist for the Introduction of Any Change Likely to Affect the Wheel-Rail Interface

Tables

Table A Terms
Table B Abbreviations

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	3 of 22

Revisions from Previous Issue

Changes to Page 1: removal of the named preparer, reviewer and authorising person and insertion of an explanatory note in relation to the status of this guidance document.

Changes made to Table A Terms and additional abbreviations added to the Table B Abbreviations (from existing text).

Changes to the Introduction to make consistent with other LRG documentation.

Numerous minor presentational, minor factual and typographical changes.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	4 of 22

TERMS AND ABBREVIATIONS

Table A – Terms

Term	Definition
Determination of Tramway	Best possible compromise between steering and vehicle lateral stability.
Gauge Restoration Corner	The manual or automated method of depositing austenitic stainless steel beads on the worn corner of the rail.
Wheel Squeal	Varying pitched noise caused by the interaction between wheel and rail.

Table B – Abbreviations

Term	Definition
GCR	Gauge Corner Restoration
IRW	Independently Rotating Wheels
Km	Kilometres
LRSSB	Light Rail Safety Standards Board
M	Metre
RCF	Rolling Contact Fatigue
ROGS	Railways and Other Guided Transport Systems (Safety) Regulations 2006 (as amended)
RTU	Rail Technology Unit
S&C	Switches and Crossings
SMS	Safety Management System
TPG	Tramway Principles and Guidance
UK	United Kingdom

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	5 of 22

1. Introduction

- 1.1. This guidance supports the high level principles set out in LRG 1.0 Tramway Principles and Guidance (TPG) published by the Light Rail Safety Standards Board (LRSSB).
- 1.2. This document provides high level guidance in relation to the interface between wheels and rails for those delegated this responsibility in relation to UK Light Rail (tramway) systems based on 'line-of-sight' operations only. As with all guidance, this document is not prescriptive and is intended to give advice not to set a mandatory industry standard, and it is based upon goal setting principles as good practice.
- 1.3. Much of this guidance is based on the experience gained from existing UK Light Rail systems and from published documents. It does not endorse or prescribe particular arrangements adopted by any of these systems and is intended to provide advice to those involved in the interface between wheels and rails.
- 1.4. This guidance is not intended to be applied retrospectively to existing Light Rail systems. However, owners and operators should consider and assess any implementation of this guidance and / or any subsequent revision, to ensure continual improvement so far as is reasonably practicable.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	6 of 22

2. Scope

- 2.1. This guide contains recommendations for good practice in the management of the wheel-rail interface which includes the reduction of derailment risk over the whole life of the Light Rail system.
- 2.2. This guidance is split into sections reflecting the life cycle of Light Rail schemes from initial specification to eventual operation. The scope of the document does not currently consider the wheel-rail interface for Tram Train vehicles and infrastructure.
- 2.3. It is not possible within this context to provide prescriptive specifications that can be followed in all cases. Light Rail systems vary considerably in their track construction, track alignment, vehicle types and operational characteristics. However, the aim of this document is to provide guidance as a checklist to ensure that wear and derailment risk are minimised as far as practicable.
- 2.4. This guidance refers to other aspects of wheel rail interface including techniques for the potential to increase the life cycle of the Light Rail assets. In addition, it also offers reference to associated negative characteristics such as the generation of excessive noise, ride quality and how this might be mitigated and improved in the case of the latter.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	7 of 22

3. Wheel-Rail Interface Specification

- 3.1. The fundamental principle of the wheel-rail interface specification is that a detailed specification should be produced at an early stage that includes compatibility of the selected wheel and rail profiles for plain line and switches and crossings (S&C).
- 3.2. The specification should state performance and expected life of both wheels and rails and also consider future maintainability. This process should also be revisited if any new vehicles or new wheel profiles are introduced onto the Light Rail infrastructure.
- 3.3. The wheel and rail profiles selected must be geometrically compatible for both plain line and S&C. With respect to the track, critical dimensions include the following (not exclusively):
 - Track gauge (for which a gauging point should be specified);
 - Width and depth of rail groove;
 - Check rail gauge; and
 - Need for flange tip running or for running on shared infrastructure (for example, a mixture of Light Rail and Heavy Rail S&C with different check rail gauges).
- 3.4. Considering the wheelset, critical dimensions include the following (not exclusively):
 - Back-to-back dimension;
 - Flange thickness and shape;
 - Tread conicity; and
 - Wheel diameter.
- 3.5. Rail profiles should be selected and wheel profiles designed to achieve the best possible compromise between steering and vehicle lateral stability (determination of tramway). This requires the co-operation of track and vehicle designers, and ideally should also include vehicle dynamic simulation of the proposed vehicles by the manufacturer to optimise the chosen wheel profile.
- 3.6. The contact conditions generated by the chosen wheel and rail profiles should be checked to ensure that they do not produce excessive contact stress or wear.
- 3.7. All parties involved in the interface specification should understand that its eventual performance is a function of how the wheel and rail profiles work together, and the profiles cannot therefore be selected in isolation.
- 3.8. When specifying new systems, provision should always be made for an underfloor wheel lathe. Without this, wheel profiles cannot be economically maintained.
- 3.9. The interface specification should consider how the system is to be maintained in the future. This would provide allowance within the infrastructure that is necessary to enable currently available on-track plant such as tamping and grinding machines to be employed, and suitable road and / or rail connections to allow supplies such as ballast and rails to be delivered to the network.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	8 of 22

- 3.10. A key consideration is the maintainability of embedded rails in street running sections. The expected life of these rails should be predicted and the track system specified to facilitate eventual replacement.
- 3.11. Standard methods for extending the life of the rail are gauge corner restoration (GCR) and general welding, so rail steel grades for tight curves would need to be chosen to allow side or head wear to be rectified by these methods. In practice, this may dictate the use of standard grade rail steel which does not require pre-heating to temperatures which degrade any surrounding rubber or polymer material. Detailed guidance on these issues may be found in the RTU (Rail Technology Unit) Report 90/3/B 'A Good Practice Guide for Managing the Wheel-Rail Interface of Light Rail and Tramway Systems'¹.
- 3.12. However it should be noted that the critical issue for optimum performance on small radius curves is to maintain the geometry of the rail head as closely as possible, and this is more effectively achieved by the use of hard steels with a lower wear rate combined with effective flange lubrication. If the rail head has worn to the extent that welding is required, then contact conditions will have been sub-optimal for a significant period, with two point contact leading to excessive wear and noise. Welding will also introduce discontinuities in the rail which could themselves lead to corrugation.
- 3.13. Gauge widening is often applied on small radius curves in heavy rail alignments, with the aim of allowing the wheelset to exploit the available conicity to steer. This may however be found to be counter-productive in Light Rail where very small radius curves preclude the wheelset steering other than through flange guidance. In this case, gauge widening simply has the effect of decreasing the clearance between the flangeback and keeper rail, leading to premature wear and failure of the keeper. Gauge widening should therefore be restricted to curves which are large enough for flange free curving to occur.
- 3.14. The design of the trackform should allow for positive gauge restraint, either by attaching rails to concrete sleepers / slab or through the use of tie-bars attached between the rails. It should be remembered that the installation of tie-bars can themselves cause rail stress raisers if not installed at sufficiently small intervals and should never be installed singularly. Depending on the design of the track layout, it may be possible to use tie-bars only at the small-mid radius curves where gauge spreading forces are greatest.
- 3.15. The basic design layout of any new system should avoid small radius curves where at all possible. Small radius curves can often lead to wheel squeal and wear problems, coupled with an increased risk of derailment. These factors contribute significantly to increased maintenance costs for both vehicle (wheel wear) and the track. Considerable benefits can be gained through relatively small modifications to track layout at the design stage.

¹ <https://uktram.com/wp-content/uploads/2018/07/Wheel-Rail-Interface-of-Light-Rail-and-Tramway-Systems.pdf>

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	9 of 22

4. Contractual Arrangements

- 4.1. Contracts should recognise the wheel-rail as a key interface and therefore contractual arrangements at all stages of the life-cycle should ensure that responsibility for the wheel-rail interface is clearly defined. Contracts should encourage active and integrated management of this interface.
- 4.2. During the design and delivery of a Light Rail scheme, there should be a nominated design authority whose remit covers both sides of the wheel-rail interface. Their responsibilities should include cross interface requirements such as vehicle mounted or infrastructure based lubrication.
- 4.3. The delivery contract for the system should include preparation of suitable wheel-rail interface maintenance standards (refer to Section 5) and sufficient technical documentation of track and bogie design to allow investigation of future interface problems.
- 4.4. Design, delivery and maintenance contracts should be checked to ensure that the key parts of the interface are the responsibility of only one party in the contract if possible, thereby reducing the risk of incompatibility issues. In cases where there is infrastructure in shared ownership, all interface responsibilities should be clearly defined to all parties.
- 4.5. Maintenance contracts should specify performance indicators that encourage active management of the interface. These might include, for example, passenger comfort and rail life, etc.
- 4.6. Where possible, maintenance of the vehicles and track should be managed by a single organisation with the appropriate skills, knowledge and expertise to carry out the majority of routine maintenance within their organisation with no sub-contracting to a third party.
- 4.7. Where maintenance of track and / or vehicles is sub-contracted by the operator to third parties, the operator should retain sufficient technical knowledge in-house to ensure the competence of the sub-contractor.
- 4.8. The competency of the sub-contractor should be subject to regular audits of completed work by the operator including inspection of the works not just the supporting documentation.
- 4.9. Any formal relationship relating to the maintenance of the wheels and track should be contractually agreed between the operator, track maintainer and vehicle maintainer / manufacturer which allows for performance and safety enhancing changes to be made across the system without commercial or political obstruction.
- 4.10. Where relevant and credible information is available, consideration should be given to specifying the anticipated life of key components in the wheel-rail interface and who rectifies them if the specification is not met. This applies particularly to rails (plain line and S&C) where there is a greater risk of problems developing over considerable time periods and where early investigation / rectification can be overlooked.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	10 of 22

- 4.11. Any contract should provide for a rational approach to managing the wheel-rail interface particularly with regard to maintenance and cost of renewals.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	11 of 22

5. Standards

- 5.1. Standards should be set which control all key components in the wheel-rail interface. This ensures that coherent wear limits are set for both sides of the interface that retain a margin of safety when wheel and rail are at their respective outer limits.
- 5.2. Track and vehicle standards must not be developed in isolation. For example, standards governing wheel flange height and rail head wear should be matched to preclude the possibility of a wheel at maximum flange height striking fishplates or rail grooves.
- 5.3. Wheel standards should specify as a minimum the following (not exclusively):
 - Limits on flange height and thickness and wheel flange angle where required;
 - Maximum sizes for defects such as wheel flats, rolling contact fatigue (RCF), tread rollover, toe-radius build up, hollow wear etc.;
 - Minimum acceptable surface finish on newly turned wheels;
 - Inspection frequencies for wheel geometry and defects; and
 - Minimum actions, with timescales, when wheel wear or defects are identified.
- 5.4. Rail standards should specify as a minimum the following (not exclusively):
 - Limits on side and head wear for plain line with additional limits for keeper rail wear in grooved rail;
 - Limits on wear through switches including at the toes, through stock rails and at the crossing nose;
 - Minimum value for the toe opening at switches;
 - Maximum permissible gap between switch and stock rails at switch toe;
 - Minimum and maximum check rail clearance in S&C and plain line;
 - Maximum sizes for defects such as RCF, lipping, rail foot defects, squats etc.;
 - Minimum standards for smoothness of cross sectional profiles following weld repairs to plain line and S&C including restoration of correct profiles at switch toes;
 - Inspection frequencies for rail wear and defects;
 - Minimum actions (with timescales) when wear or defects are identified;
 - Gauge corner radius;
 - Heights of raised check rails; and
 - Corrugations.
- 5.5. Track geometry standards should specify the following (not exclusively):
 - Minimum permissible curve radii. This will be dependent on many factors, including the vehicle axle and bogie spacing, suspension design, wheel flange design, rail groove width, wheel-rail conicity etc. Absolute minimum values are therefore system dependent, and it is essential that these parameters are studied before quoting a minimum curve radius;

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	12 of 22

- The combination of vertical and horizontal curvature together with cant should be considered, so as not to impart unnecessary wheel unloading in curved track sections;
- Permissible ranges of design values for gauge, cant, rate of change of cant, cant deficiency and rate of change of deficiency (vehicle and track dependent);
- The largest track twist permissible (vehicle dependent);
- Whether or not gauge widening is to be applied in small radius curves, this should consider the vehicle configuration, curve radii and wheel-rail conicity, in general low conicity systems (DIN² type wheel and rail profiles) will not benefit from gauge widening;
- Maximum values for vertical and lateral irregularities and minimum and maximum values for gauge;
- Inspection frequencies for track geometry defects; and
- Minimum actions, with timescales, when defects are identified.

5.6. Standards should specify simple wheel and rail inspection gauges where appropriate, such as the following (not exclusively):

- Flange height / thickness gauge;
- Rail side and headwear gauges;
- Switch tip wear go / no-go gauge; and
- Wheelset back-to-back gauge.

5.7. It is essential that standards define how the interface is to be maintained in a safe condition (within the agreed limits for optimum performance). In addition, standards should also specify the required competencies of those who have the responsibility for the inspection, maintenance and sign-off of both the track and vehicles in order to ensure that the wheel-rail interface is upheld.

5.8. Each organisation should have a process in place for reviewing and updating standards related to the wheel-rail interface. Responsibility should be placed with designated individuals either from within the organisation or from an external source, with sufficient knowledge and competence to carry out the task. The ownership of standards should form part of the operator's safety management system (SMS) such that it is re-allocated when individual staff members leave the company.

5.9. There are a number of products currently available to Light Rail systems that have been manufactured to assist with the maintenance of the wheel-rail interface. Products that include flange lubrication and friction modifiers can be installed on rolling stock and the infrastructure to facilitate the extension of the life of the rail, as well as reducing noise and assisting with braking.

5.10. Any reasons for changes in standards should be adequately and sufficiently documented in technical reports which should be retained within the SMS so that the history of a given standard is recorded for any future reference.

² Deutsches Institut für Normung (German Institute for Standardisation)

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	13 of 22

6. Inspection and Monitoring

- 6.1. Formal inspection and monitoring regimes should be implemented which identify any gross defects, ongoing degradation and emerging wear problems in an efficient and timely manner.
- 6.2. It is essential that appropriate and sufficient equipment is available and employed to allow adequate and appropriate inspection and monitoring of the wheel-rail interface.
- 6.3. Strategic management of the system by engineers is likely to include off-the-shelf equipment such as the following (not exclusively):
 - Cant and gauge sticks;
 - Track geometry trolleys;
 - Miniprof wheel and rail profile measuring devices; and
 - Ride comfort meters, etc.
- 6.4. Simple maintenance checking devices for use by track workers are likely to be custom made for the particular system, and would include hand-held gauges.
- 6.5. Use of electronic wheel and rail profile measuring equipment is useful in determining wear patterns and wear rates. An example, of such equipment is the MiniProf manufactured by Greenwood Engineering.
- 6.6. All Light Rail systems should have a means of measuring track geometry which is suitable for both flat bottomed and grooved rail. Standard track geometry trolleys may require modification for use on tight curves, with grooved rail, on Light Rail S&C and on raised check rails.
- 6.7. The level of sophistication of track geometry trolleys varies considerably. For example, a lightly trafficked system constructed entirely on slab track requires less rigorous inspection than a heavily trafficked one on ballasted track. A minimum requirement should be for a trolley to measure track gauge, check / keeper rail gauge and track twist.
- 6.8. It should be noted that the ability of track geometry trolleys to measure short wavelength lateral and vertical irregularities and long wavelength curvature is often very limited. This should be reflected in maintenance standards which specify limits that can actually be inspected using the available equipment.
- 6.9. Measurement of passenger comfort using either temporary or permanently installed on-board equipment may prove useful in detecting both gross vertical and lateral alignment faults and trends in deterioration. However, it should be noted that as such measurements are effectively filtered by the vehicle suspension, they should not be relied upon as the sole means of detecting emerging wear problems. Certain wear problems may reach an advanced stage before they can be reliably detected by passenger comfort measurements, and having reached this point may be very difficult to correct.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	14 of 22

- 6.10. All staff carrying out inspection of the wheel-rail interface should hold the relevant competencies and should have received specific training on the common causes of interface problems in general and derailment risks in particular.
- 6.11. In addition to the frequent track walks carried out by patrolmen to identify gross faults and maintenance requirements, including items such as loose rail clips or fixings, there should be a programme of inspection to identify longer term issues associated with build-up of wear to rails and wheels. This would normally be carried out by engineers with specialist wheel-rail interface knowledge.
- 6.12. Managers responsible for the safety of the interface should not rely solely on reports from patrolmen but should ensure they frequently update their own knowledge by track walking and examining vehicles. This also presents the opportunity to ensure that track and rolling stock technicians have an appreciation of the issues surrounding safety of the interface and derailment prevention.
- 6.13. Typical wear rates should be calculated and recorded for wheels and for rails. For wheels this should include separate rates of change for flange height and thickness for motor bogies, trailer bogies and bogies with Independently Rotating Wheels (IRWs) as applicable.
- 6.14. For rails this should include side and head wear for straight track and a variety of curve radii for both flat bottomed and grooved rail. When selecting sites for calculating rail wear, the effects of cant deficiency, varying traffic tonnage, rail grade and lubrication should be considered.
- 6.15. In circumstances where the system has deteriorated to a point where contact occurs on keeper rails, keeper rail wear rates should be calculated and inspection enhanced until the problem can be rectified.
- 6.16. Inspection regimes must recognise the increased derailment risk presented by S&C. Critical areas include the planed part of the switch and the crossing nose with particular emphasis on the initial 1-2m at the switch toes where the blade is weakest and the impact forces are highest. Attention must be given to damage to switch, stock and crossing rails, lipping that obstructs the correct seating of the blade against the stock rail and maintenance of toe opening and check rail clearances. The ongoing compatibility between the worn wheel flange shape (flange angle and thickness changes) and the switch toe should also be monitored.
- 6.17. All inspection and monitoring activities should record information about the performance of the wheel-rail interface in a detailed and systematic manner. This should not just include faults and maintenance requirements but also wear rates, track geometry, maintenance records, wheel and rail profiles, details of technical investigations etc. This latter set of information is essential to ensure that emerging interface problems can be identified and investigated.
- 6.18. It is advisable to enhance inspection frequencies when events occur which may affect the equilibrium of the interface, which could include the following (not exclusively):
- Grinding;

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	15 of 22

- Milling;
- Major renewals;
- Extensions to the network;
- Changes in wheel turning regime (for example, due to a change in wheel profile or wheel lathe faults); and / or
- The introduction of new types of vehicles.

6.19. A checklist of items to be considered when introducing new vehicle fleets onto existing systems is given in Appendix 1.

6.20. Major rail renewals or the introduction of a greater than normal population of new wheels (for example, from new vehicles or bogie overhauls), may have a significant effect on wear rates on both sides of the interface.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	16 of 22

7. Maintenance

- 7.1. Vehicle and track maintenance should be carried out in an integrated manner to established standards that ensure the safe operation of the wheel-rail interface.
- 7.2. Responsibility for every component in the wheel-rail interface should be clearly defined.
- 7.3. Wheel lathe operators should record appropriate information about each wheel turned including the following (not exclusively):
 - Date of turning;
 - Km run since last turning;
 - Pre and post turning diameter;
 - Defects; and
 - The depth of cut required to remove them.
- 7.4. Vehicles may become susceptible to derailment if wheel loads are not evenly distributed within each bogie. Some vehicle primary suspension designs may require the use of wheel weighing equipment or a specially designed test rig to ensure even load distribution following bogie overhaul or attention to the primary suspension.
- 7.5. Wheel turning should restore the full flange thickness in order to guard against derailments (for example, through increased flange angle interacting with S&C) and to help minimise the possibility of flangeback contact with the keeper rail.
- 7.6. Consideration should be given to regular planned wheel turning to maintain conicity and / or desirable contact conditions. This may be considerably more frequent than required to stay within flange height and thickness limits.
- 7.7. A number of factors should be taken into account when determining the optimum wheel turning regime. For example, where reliable on-board and / or track mounted lubrication is used, wheel turning intervals may be extended, whereas a system having tight curves and poor lubrication may require frequent wheel turning. A governing factor in this latter case is often the avoidance of excessive depth of cut (and hence reduction in wheel diameter and life) to restore a full flange thickness.
- 7.8. When considering wheel turning regimes, it should be noted that the rail will wear to the average shape of the worn wheels in the fleet. Therefore, if wheels run very large mileages between turning their shape, the worn shape of the rail may change very radically from the original design profile. Newly turned wheels will then be geometrically mismatched with the worn rail shape leading to high contact stresses and wear rates on both sides of the interface. Thus, high mileages between turnings are only recommended if the worn wheel exhibits only modest changes in shape from the new profile. These conditions are less likely on Light Rail systems where a variety of track types and alignments are encountered. In practice, it is often found that a regular turning regime provides optimum interface performance. The management of the interface in this way can also be achieved through rail grinding / milling.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	17 of 22

- 7.9. Wheel lathes should produce a smooth profile that meets the surface finish requirements defined in standards (refer to Section 5). Steps or grooves, particularly on the wheel flange should not be accepted as they promote derailment.
- 7.10. On-vehicle flange lubricators should be inspected and maintained frequently. Where stick-lube is used, a simple setting gauge should also be used to check the correct positioning of the stick. If wheels are required to run for very long periods without turning (for example, through failure of a wheel lathe), the position of the stick should be adjusted to prevent a large, flat, unworn facet developing at the flange root in the position where the lubrication is applied.
- 7.11. IRW have a tendency to offset running, whereby the lack of steering forces associated with IRW's leads to the bogie running in arbitrary positions within the gauge (offset) and may not therefore collect lubricant effectively from trackside lubricators. In this case, wear issues may need to be addressed with on-board stick or grease wheel lubrication systems.
- 7.12. In conditions where increased derailment risk might exist, for example, from newly ground switches, or when check / guard rails have been removed for maintenance etc., supplementary lubrication should be applied to the gauge corner / face of the rail by hand.
- 7.13. Street running systems should normally be maintained to avoid wear of the keeper rail by controlling sidewear, wheel flange wear and gauge spreading. Wear of keeper rails will eventually lead to their failure, at which point a wheel flange is likely to strike the broken keeper, leading to derailment.
- 7.14. A feature of many derailments is discrete track twist or cyclic twist / top track geometry which causes wheel unloading. It should be noted that the degree of wheel unloading in response to track twist is largely independent of speed and therefore, temporary speed restrictions may only mitigate the consequences of a derailment rather than preventing it happening.
- 7.15. Repairs to S&C by welding and grinding carry a particular risk due to the possibility of producing a profile on the switch blade which encourages flange climbing, coupled with increased friction as a result of the 'rough' surface produced by grinding. Such repairs should always be carried out by persons who have an assessed competency in weld repair of S&C. The completed work should be inspected and signed off by a competent engineer, and only after a check has also been made of both the profile of the repaired rail including assessment of surface roughness (for friction conditions) together with the mechanical operation of the switch. Consideration should be given to hand lubrication of the ground gauge face for a short period following repair.
- 7.16. Rail grinding is commonly used on Light Rail systems to attempt to restore the original rail profile to prevent the creation of a 'new' wheel rail interface. However, grinding is never enough to entirely remove all material metallurgically changed by the corrugation. Therefore, whilst beneficial, grinding may change the rail profile shape in a manner that is undesirable from the point of view of the contact conditions. Grinding contractors work should be carefully audited to ensure changes are understood and changes made if

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	18 of 22

appropriate (for example, lubrication if conicity reduced). Consideration may be given to techniques such as offset grinding which attempt to restore the original rail profile.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	19 of 22

8. Operation Management

- 8.1. The wheel-rail interface should be actively managed to ensure its safety both during normal operations and during periods of change. The management of the interface should not be impaired by the traditional divide between track and vehicle engineering; refer also to Sections 4.2 – 4.6.
- 8.2. Wear of wheels and rails (which cause both derailment risks and interface problems) is usually progressive over a period of time. Efficient record keeping is therefore essential to the management of wheels and rails.
- 8.3. If possible, records for both sides of the interface should be stored together to allow both track and vehicle engineers access to the information and to encourage the interface to be viewed as a system.
- 8.4. Management of the wheel-rail interface will be improved if the separation of vehicle and track engineering functions is reduced. This may be achieved by designating responsibility for the performance of the interface to a single engineering manager or setting up regular interface management meetings where track and vehicle engineers evaluate wheel-rail performance.
- 8.5. Both professional and technician staff should receive appropriate training in the wheel-rail interface management with particular emphasis on avoiding conditions likely to promote derailment.
- 8.6. When changes occur that may impact the performance of the wheel-rail interface, appropriate short term actions should be taken to ensure that the system remains within safe limits and that any accelerated wear is identified and managed. This includes the following (not exclusively):
 - Introduction of new fleets;
 - Extensions to the network;
 - Major bogie overhauls;
 - Significant re-railing or track renewal; and
 - Changes to the established maintenance practices (wheel turning, wheel profile, rail grinding etc.).
- 8.7. Another type of major system change to be considered is the extension of an existing Light Rail system. Although the advice provided in Appendix 1 is applicable, a key consideration is ensuring compatibility of new and existing interfaces. Where different rail profiles are selected for the extension (usually on the grounds of cost and / or availability), the geometric compatibility checks described in Section 3 should be carried out to confirm their suitability.

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	20 of 22

APPENDIX 1

Checklist for the Introduction of Any Change Likely to Affect the Wheel-Rail Interface

A number of system issues and checks should be considered when new vehicle fleets, a change of wheel or rail profile has been introduced onto an existing Light Rail system. The following is intended to provide a guidance checklist of items from the perspective of the wheel-rail interface.

Elements of this checklist can also be used where there is a new section of route being implemented. However, there are other elements that need to be considered as highlighted in this document, for example, compatibility of new and existing interfaces.

1. Existing Interface Conditions

- Is a monitoring and data collection regime in place?
- Parameters for monitoring might include, wheel and rail profiles, track geometry, rail and wheel defects, noise, lubrication, rail clip / fastening breaks, renewal rates, route tonnages, braking / acceleration patterns, friction levels etc.
- Checks should be made that rail clip / fastenings are not broken, and whether they are loose / out of alignment.
- Is the monitored data (wheel and rail) stored in a central location and analysed in a manner that yields an understanding of the prevailing interface conditions for both track and vehicle engineers?
- Has the relevant data (particularly track geometry and wheel-rail profiles) been made available to the vehicle manufacturer?

2. Geometric Compatibility

- Will the new fleet use existing wheel profiles?
- If so, does this profile give optimum performance if the vehicle design is significantly different to existing vehicles?
- Could overall system costs be optimised by a new wheel profile or revised turning interval?
- If a new profile is to be introduced, has analysis been carried out to check derailment risk under the full range of expected conditions? Is the new profile compatible with the existing S&C geometry?

3. Vehicle Design

- Is the vehicle designed using a realistic conicity range?
- Has wheel size (diameter and thickness) been considered (to avoid any compromising the wheel rail interface and the efficiency of check rail arrangements?
- Could the design be improved by controlling the conicity by other means (for example, rail grinding)?

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	21 of 22

- Has a passenger comfort benchmark been set against existing fleet performance (often neglected in new tram performance)?
- How does the curving ability of the new fleet compare with the existing vehicles (important implications for wheel life, rail wear, RCF etc.)?
- How tolerant are the new trams of degraded track conditions, i.e. how far 'out of spec' can the track be before the vehicle derails? – important if new trams are less tolerant than the old fleet for example, in their ability to negotiate track twist.
- Has adequate provision been made for on-board flange lubrication?
- Has a process been considered for the selection retrospective installation of an on board system to record data with the ability to measure interface related parameters (for example, vertical acceleration, suspension displacement). Would such provision be useful in improving infrastructure monitoring?

4. Wheel and Rail Wear

- Are existing wheel and rail wear rates calculated and understood?
- Have wear predictions (for wheels and rails) been carried out using simulations of the actual route from measured track geometry?
- Will the new fleet improve or degrade wheel-rail life?
- Unless the curving and wear performance of the new fleet is identical to the old, changes in the track maintenance regime are likely to be required (for example, flange contact may occur at larger curve radii requiring additional lubricators).
- Have the track engineers been made aware of the likely changes?

5. Track Degradation, Rail Damage and RCF

- Are existing track degradation and damage conditions understood?
- How do new and existing fleets compare in terms of their impact on the track (steering ability, wheel load, contact stress, unsprung mass, suspension stiffness, simulated track forces etc.)?
- Have the vehicle design decisions been tested in any existing track deterioration / asset management models?
- Has consideration been given to the design of wheelsets with regard to limiting noise and propensity to generate corrugation?

6. Monitoring and Maintenance Regime

- Is a robust monitoring regime in place on both wheel and rail sides of the interface that will collect data from the day the first new vehicle is introduced on test (if data is not collected then the opportunity to solve problems as they arise can be limited)?
- Will the data be centrally stored and analysed to ensure joint understanding by track and vehicle engineers?
- Are track engineers informed and prepared for the likely changes needed to the track maintenance regime when the new fleet is introduced?

	WHEEL-RAIL INTERFACE GUIDANCE	LRSSB - LRG - 16.0	
		Issue	01
		Revision	01
		Date	24/05/2023
		Page	22 of 22

- In the unlikely event that a new fleet is introduced in rapid succession, the age profile of the wheels will change rapidly (i.e. majority of new wheels). This can result in short term changes, such as increased wear levels while the fleet 'beds in'. Are contingency measures in place?
- Are contingency measures in place in case of a sudden emergence of interface problems (wheel or rail rolling contact fatigue, corrugation, wear)?
- Consideration must be given to any transition effects when the profile for new vehicles is being determined.